



FINISHED OPENING SIZE: (W) (H)

Insulated Foam Panel Thickness

40mm 80mm

Vision Window Height
(standard no window)

220mm 440mm 660mm

UL LISTED OPERATOR INPUT POWER

220V-240V SINGLE PHASE

CONTROLS:

STEP CONTROL (PULL TO OPEN, PULL TO CLOSE)

TIMER TO CLOSE (PULL TO OPEN, TIME DELAY TO COLSE)

3-BUTTON CONTROL (OPEN, COLSE, STOP)

RADOR OPEN AND TIMER CLOSE

FLOOR LOOP OPEN AND TIMER CLOSE

REMOTE CONTROL

SAFETY DEVICES:

BOTTOM SAFETY EDGE AND
SAFETY BEAM ARE STANDARD

LIGHT CURTAIN

EXTRA SAETY BEAM

MOUNTING FASTENERS:

CONCRETE ANCHOR

METAL JAMBS

OPTIONS:

HEADER HOOD

STAINLESS STEEL TRACK
COVER AND HEADER HOOD

OTHER REQUIRED OPTIONS:

QUANTITY:

M/F:

CUSTOMER:

JOB:

DATE:

SIGNATURE:

SHIP TO:

QUOTE: ORDER: #:

TDK HSR-L High Speed Spiral
Roll Up Door Shop Drawing

TDK DOORS